

Recessed 4" Deep Cell Parabolic

FEATURES

- Meets IES standard RP-1 glare control recommendations on most models
- Ideal for today's computer intensive offices
- Wide light distribution provides uniform illumination
- 4" deep low iridescent anodized aluminum louver
- Surface mount available
- Mechanical light trap prevents light leaks
- Black reveal with full air handling capabilities
- UL listed 1598, cUL or CSA. Damp Location standard



ORDERING INFORMATION

45										
MODEL	NO. OF LAMPS	CEILING TYPE	CELLS WIDE BY CELLS LONG	AIR CONTROL	VOLTAGE	OPTIONS				
45 Recessed 4" Deep Cell Parabolic	1 One 2 Two 3 Three 4 Four 6 Six 8 Eight <small>See Product Availability table below.</small>	G Grid F Overlap Flange M Modular Fit-in Trim SM Surface Mount (Static only) SG Slot Grid	See Product Availability table below.	V Supply Vanes D Extract Dampers VD Vanes & Dampers	U 120V-277V 347 347V	F0735 35K 75CRI T8 Lamps Installed F0835 35K 82CRI T8 Lamps Installed F5835 35K 85CRI T5 Lamps Installed 2BC Two Ballast Covers C388 3-Wire Flex C488 4-Wire Flex EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse MS9 Master/Satellite w/9' Harness PAF Paint After Fabrication NYC NYC Compliant NYCU NYC Compliant, Union Label				
SIZE	LAMP TYPE	LOUVER FINISH	AIR FUNCTION	BALLAST						
14 1' x 4'	17 2', T8: 17 Watt	LD Low Iridescent Semi-Specular (Std.)	S Static	NOTE: See Technical Section for other ballast options.						
22 2' x 2'	28 4', T5: 28 Watt	LS Low Iridescent Specular	A Air Handling	E Electronic T8, Instant Start						
24 2' x 4'	31U1 U-Bent, 1 5/8" Leg Spacing T8: 31 Watt	MA Matte Anodized Low Iridescent Semi-Specular Aluminum	C Combination Supply/Extract	3E 3-Lamp Electronic T8, Instant Start						
44 4' x 4'	32 4', T8: 32, 30, 28 or 25 Watt 32U6 U-Bent, 6" Leg Spacing T8: 32 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 or 51 Watt		H Heat Extract	4E 4-Lamp Electronic T8, Instant Start 24E (1) 2-Lamp and (1) 4-Lamp Electronic T8, Instant Start EP Electronic T5 or T8, Programmed Start 3EP 3-Lamp Electronic T5HO or T8, Programmed Start 4EP 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start 3ETT 3-Lamp Electronic Twin Tube, Instant Start (Specify voltage)						
					For a specific ballast vendor show as option.					

PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	LOUVER CONFIGURATIONS
1' x 4'	1	28, 32, 54	1 x 6 (6), 1 x 9 (9)
	2	28, 32, 54	1 x 6 (6), 1 x 9 (9)
2' x 2'	2	17, 31U1, 32U6, 40TT	3 x 3 (9) , 4 x 4 (16)
	3	17, 31U1, 40TT	3 x 3 (9) , 4 x 4 (16)
	4	28, 32, 54	2 x 6 (12) , 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)
2' x 4'	2	28, 32, 54	2 x 6 (12) , 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)
	3	28, 32, 54	3 x 6 (18) , 3 x 8 (24)
	4	28, 32, 54	2 x 6 (12) , 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)
4' x 4'	6	28, 32, 54	6 x 6 (36) , 8 x 8 (64)
	8	28, 32, 54	6 x 6 (36) , 8 x 8 (64)

Standard louver configurations shown in bold. For other lamp or louver configurations, contact your local Columbia Lighting representative. Various options may increase fixture height on 2' x 2' units. Contact your Columbia Lighting representative if plenum depth is a concern.

