

COV

Covelight

RECESSED ARCHITECTURAL








FEATURES

- Unique design provides wide distribution, far superior to standard or staggered strip lights
- Notched reflector eliminates socket shadows
- Maximum efficiency
- Shallow 3⁷/₁₆" (T8) or 1⁷/₈" (T5) housing profile
- T8, T5 or T5HO
- Modular lengths simplify installation
- Quick disconnect plugs make row wiring easy
- Hinged reflector allows quick access to wireway
- Built-in aligner tabs align fixture housings, simplify continuous row installation
- UL listed 1598, cUL or CSA. Damp Location standard

ORDERING INFORMATION

MODEL	SIZE	NO. OF LAMPS IN CROSS SECTION	LAMP TYPE	BALLAST	VOLTAGE	OPTIONS
COV Covelight	2 2' 3 3' 4 4' 6 6' 8 8'	1 One 2 Two (N/A with TT lamps) See Product Availability table below.	14 2', T5: 14 Watt 17 2', T8: 17 Watt 21 3', T5: 21 Watt 24 2', T5HO: 24 Watt 25 3', 25 Watt, T8 28 4', T5: 28 Watt 32 4', T8: 32, 30, 28 or 25 Watt 39 3', T5HO: 39 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 Watt	NOTE: See Technical Section for other ballast options. E Electronic T8, Instant Start ED Electronic Dimming T8 and T5 EP Electronic T5, T5HO, or T8, Programmed Start ETT Electronic Twin Tube, Instant Start	U 120V-277V 347 347V	EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse MS Master/Satellite (2 fixtures, 1 ballast) SMS Satellite/Master/Satellite (3 fixtures, 1 ballast) SMSS Satellite/Master Satellite/Satellite (4 fixtures, 1 ballast) NYC NYC Compliant NYCU NYC Compliant, Union Label



PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS IN CROSS SECTION	NO. OF LAMPS IN FIXTURE	LAMP TYPE	WIDTH	LENGTH	HEIGHT
2'	1	1	17, 40TT	7 ⁵ / ₁₆ "	24"	3 ⁷ / ₁₆ "
	1	1	14, 24	6 ¹ / ₄ "	22 ¹¹ / ₁₆ "	1 ⁷ / ₈ "
	2	2	14, 17, 24	7 ⁵ / ₁₆ "	24"	3 ⁷ / ₁₆ "
3'	1	1	25	7 ⁵ / ₁₆ "	36"	3 ⁷ / ₁₆ "
	1	1	21, 39	6 ¹ / ₄ "	34 ¹ / ₂ "	1 ⁷ / ₈ "
	2	2	21, 25, 39	7 ⁵ / ₁₆ "	36"	3 ⁷ / ₁₆ "
4'	1	1	32	7 ⁵ / ₁₆ "	48"	3 ⁷ / ₁₆ "
	1	1	28, 54	6 ¹ / ₄ "	45 ⁵ / ₁₆ "	1 ⁷ / ₈ "
	2	2	28, 32, 54	7 ⁵ / ₁₆ "	48"	3 ⁷ / ₁₆ "
6'	1	2	25	7 ⁵ / ₁₆ "	72"	3 ⁷ / ₁₆ "
	1	2	21, 39	6 ¹ / ₄ "	69 ³ / ₄ "	1 ⁷ / ₈ "
	2	4	21, 25, 30	7 ⁵ / ₁₆ "	72"	3 ⁷ / ₁₆ "
8'	1	2	32	7 ⁵ / ₁₆ "	96"	3 ⁷ / ₁₆ "
	1	2	28, 54	6 ¹ / ₄ "	92 ⁷ / ₈ "	1 ⁷ / ₈ "
	2	4	28, 32, 54	7 ⁵ / ₁₆ "	96"	3 ⁷ / ₁₆ "