

Fluorescent Wall Wash

PARABOLICS

FEATURES

- Wall wash luminaire
- Directs majority of light to vertical surface
- Brighter walls open up spaces, minimize contrast ratios
- Versatile and economical
- Presents a clean, uninterrupted reflecting surface
- Contractor friendly
- Wireway completely accessible from below
- Suitable for individual or continuous row mounting
- UL listed 1598, cUL or CSA. Damp Location standard



ORDERING INFORMATION

FW									
MODEL FW Fluorescent Wall Wash	NO. OF LAMPS 1 One 2 Two (Not available in Twin Tube) See Product Availability table below.	CEILING TYPE G Grid SM Surface Mount (For hard ceiling use flange kit.)	REFLECTOR FINISH LS Low Iridescent Specular MA Matte Anodized Low Iridescent Semi-Specular Aluminum MW Matte White	VOLTAGE U 120V-277V 347 347V	OPTIONS EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse MS9 Master/Satellite Pair with 9' Harness MSEE Master/Satellite End-To-End NYC NYC Compliant NYCU NYC Compliant, Union Label	SIZE 102 10" × 2' 104 10" × 4'	LAMP TYPE 14 2', T5: 14 Watt 17 2', T8: 17 Watt 24 2', T5HO: 24 Watt 28 4', T5: 28 Watt 32 4', T8: 32 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 Watt	BALLAST NOTE: See Technical Section for other ballast options. E Electronic T8, Instant Start EP Electronic T5 or T8, Programmed Start ETT Electronic Twin Tube, Instant Start (Specify voltage) EPTT Electronic Twin Tube, Programmed Start	ACCESSORIES (ORDER SEPARATELY) FK102 Flange Adaptor for Hard Ceilings, 2' Fixture FK104 Flange Adaptor for Hard Ceilings, 4' Fixture

PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS IN CROSS SECTION	NO. OF LAMPS IN UNIT	LAMP TYPE	HEIGHT	LENGTH
10" × 2'	1	1	14, 17, 24, 40TT	4 ⁹ / ₁₆ "	24"
	2	2	14, 17, 24	4 ⁹ / ₁₆ "	24"
10" × 4'	1	1	28, 32, 54, 40TT	4 ⁹ / ₁₆ "	48"
	2	2	28, 32, 54	4 ⁹ / ₁₆ "	48"

