

## Fluorescent Wall Wash

PARABOLICS



### FEATURES

- Wall wash luminaire
- Directs majority of light to vertical surface
- Brighter walls open up spaces, minimize contrast ratios
- Versatile and economical
- Presents a clean, uninterrupted reflecting surface
- Contractor friendly
- Wireway completely accessible from below
- Suitable for individual or continuous row mounting
- UL listed 1598, cUL or CSA. Damp Location standard

### ORDERING INFORMATION

<b>FW</b>									
<b>MODEL</b> FW Fluorescent Wall Wash	<b>NO. OF LAMPS</b> 1 One 2 Two (Not available in Twin Tube) See Product Availability table below.	<b>CEILING TYPE</b> G Grid SM Surface Mount (For hard ceiling use flange kit.)	<b>REFLECTOR FINISH</b> MA Matte Anodized Low Iridescent Semi-Specular Aluminum MW Matte White	<b>VOLTAGE</b> U 120V-277V 347 347V	<b>OPTIONS</b> EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse MS9 Master/Satellite Pair with 9' Harness MSEE Master/Satellite End-To-End NYC NYC Compliant NYCU NYC Compliant, Union Label	<b>SIZE</b> 102 10" × 2' 104 10" × 4'	<b>LAMP TYPE</b> 14 2', T5: 14 Watt 17 2', T8: 17 Watt 24 2', T5HO: 24 Watt 28 4', T5: 28 Watt 32 4', T8: 32 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 Watt	<b>BALLAST</b> <b>NOTE:</b> See Technical Section for other ballast options. E Electronic T8, Instant Start EP Electronic T5 or T8, Programmed Start ETT Electronic Twin Tube, Instant Start (Specify voltage) EPTT Electronic Twin Tube, Programmed Start	<b>ACCESSORIES (ORDER SEPARATELY)</b> FK102 Flange Adaptor for Hard Ceilings, 2' Fixture FK104 Flange Adaptor for Hard Ceilings, 4' Fixture

For other options see pages 96-112.

### PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS IN CROSS SECTION	NO. OF LAMPS IN UNIT	LAMP TYPE	HEIGHT	LENGTH
10" × 2'	1	1	14, 17, 24, 40TT	4 <sup>9</sup> / <sub>16</sub> "	24"
	2	2	14, 17, 24	4 <sup>9</sup> / <sub>16</sub> "	24"
10" × 4'	1	1	28, 32, 54, 40TT	4 <sup>9</sup> / <sub>16</sub> "	48"
	1	2	40TT	4 <sup>9</sup> / <sub>16</sub> "	48"
	2	2	28, 32, 54	4 <sup>9</sup> / <sub>16</sub> "	48"

