

Recessed HID Parabolic

FEATURES

- Ideal for manufacturing areas, retail stores, and gymnasiums
- Metal halide lamp
- Horizontal or vertical lamp position
- Tempered glass overlay
- Ballast accessible from below
- Ballast housing is made of aluminum for maximum heat dissipation
- Black reveal with air handling capabilities
- White powder coat finish, painted after fabrication
- Uses EISA compliant pulse start metal halide technology
- UL listed 1598, cUL or CSA. Damp Location standard



ORDERING INFORMATION

MODEL	LAMP TYPE	CEILING TYPE	CELLS WIDE BY CELLS LONG	AIR FUNCTION	VOLTAGE
HH Horizontal Lamp Orientation HV Vertical Lamp Orientation	P Pulse Start, Metal Halide	F Flange G Grid	See Product Availability table below.	S Static A Air Handling	U 120V-277V 347 347V 480 480V QT Quad-Tap, 120V, 208V, 240V, 277V
SIZE	LAMP WATTS	LOUVER FINISH	AIR CONTROL	OPTIONS	
22 2' x 2'	175 175 Watt 200 200 Watt 250 250 Watt 320 320 Watt 350 350 Watt 400 400 Watt	LD Low Iridescent Semi-Specular LS Low Iridescent Specular	Blank None V Supply Vanes	GLR Fast Blow Fuse QR Quartz Restrike NYC NYC Compliant NYCU NYC Compliant, Union Label	

For other options see pages 96-112.

PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	LAMP WATTAGE	LOUVER CONFIGURATIONS
2' x 2'	1	P	175, 250, 320, 400	3 x 3 (9), 4 x 4 (16)

If desired lamp or louver configuration is not shown above, contact your local Columbia Lighting representative.

