

HH/HV LENSED

Recessed HID Lensed Troffer

LENSED TROFFERS



FEATURES

- Ideal for manufacturing areas, retail stores, and gymnasiums
- Horizontal or vertical lamp position
- Choice of tempered glass or acrylic lens with tempered glass overlay
- Ballast accessible from below
- Ballast housing is made of aluminum for maximum heat dissipation
- White powder coat finish, painted after fabrication
- Uses EISA compliant pulse start metal halide technology
- Louvered version also available, see Parabolics section
- UL listed 1598, cUL or CSA. Damp Location standard

ORDERING INFORMATION

	22	P				S		
MODEL	LAMP TYPE	CEILING TYPE	SHIELDING	VOLTAGE	OPTIONS			
HH Horizontal Lamp Orientation HV Vertical Lamp Orientation	P Pulse Start Metal Halide	G Grid F Flange	TG73 Tempered Glass, Pattern 73 CTGY12 Clear Tempered Glass with A12 Underlay DP Drop Polycarbonate Lens ²	347 347V 480 480V QT Quad-Tap, 120V, 208V, 240V, 277V	GLR Fast Blow Fuse QR Quartz Restrike NYC NYC Compliant NYCU NYC Compliant, Union Label For other options see pages 99-114.			
SIZE	LAMP WATTS	DOOR	AIR HANDLING	WIRED TO				
22 2' x 2'	175 175 Watt 200 200 Watt 250 250 Watt 320 320 Watt 350 350 Watt 400 400 Watt ¹	FS White Flush Steel FA White Flush Aluminum RA White Regressed Aluminum	S Static	277 277V (Std.) 120 120V 208 208V 240 240V				

¹400W horizontal positioned lamp listed for Marked Spacing only. See specification sheet for details.

²Available with FS door only.

