

## Recessed Parabolic Stack Light

PARABOLICS

### FEATURES

- Meets IES standard RP-1 glare control recommendations
- Ideal for library, retail, and office stack areas
- Narrow light distribution provides unequalled uniformity down the stack
- Minimal aperture width, 8" or 12"
- Installation typically requires no alteration of ceiling tiles
- Anodized low iridescent aluminum louver
- White powder coat finish, painted after fabrication
- Surface and pendant mount available, also direct/indirect
- UL listed 1598, cUL or CSA. Damp Location standard



### ORDERING INFORMATION

<b>LSL</b>	-		-		-		-		-		-	
<b>MODEL</b> LSL Recessed Parabolic Stack Light	<b>NO. OF LAMPS</b> 1 One 2 Two See Product Availability table below.	<b>CEILING TYPE</b> F Flange G Grid GT Integral Cross-tee (Grid ends lay into standard T-Bar, sides act as integral cross-tee to support tile) SM Surface Mount (Static only)	<b>CELLS WIDE BY CELLS LONG</b> See Product Availability table below.	<b>AIR FUNCTION</b> S Static H Heat Extract (No dampers)	<b>VOLTAGE</b> U 120V-277V 347 347V	<b>SIZE</b> 84 8" x 4' 14 1' x 4'	<b>LAMP TYPE</b> 28 4', T5: 28 Watt 32 4', T8: 32, 30, 28 or 25 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 or 51 Watt	<b>LOUVER FINISH</b> LD Low Iridescent Semi-Specular (Std.) LS Low Iridescent Specular GW Gloss White	<b>BALLAST</b> <b>NOTE:</b> See Technical Section for other ballast options. E Electronic T8, Instant Start EP Electronic T5 or T8 Programmed Start ETT Electronic Twin Tube, Instant Start (Specify voltage)	<b>OPTIONS</b> F0735 35K 75CRI T8 Lamps Installed F0835 35K 82CRI T8 Lamps Installed F5835 35K 85CRI T5 Lamps Installed EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse MS9 Master/Satellite w/9' Harness MSEE Master/Satellite End-to-End NYC NYC Compliant NYCU NYC Compliant, Union Label		

For other options see pages 99-114.

### PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	LOUVER CONFIGURATIONS	DEPTH
8" x 4'	1	28, 32, 54	1 x 8 (8)	6 1/4"
	2	40TT	1 x 8 (8)	6 1/4"
1' x 4'	1	28, 32, 54	1 x 9 (9)	8"

