

## Specification Grade Circular Regressed Static Troffer

### FEATURES

- Meets demanding architectural and aesthetic requirements
- 9" deep housing ensures no lamp imaging in lens
- Deep plaster flange accommodates various ceiling thicknesses
- 18-gauge steel plaster ring eliminates light leaks
- Steel lens clips hold lens firmly in place
- Thick, arched acrylic diffuser conceals light source yet permits high transmission of light
- White powder coat finish, painted after fabrication
- UL listed 1598, cUL or CSA. Damp Location standard



### ORDERING INFORMATION

<b>M46</b>			<b>F</b>	<b>FS</b>	<b>OP</b>		
<b>MODEL</b>	<b>NO. OF LAMPS</b>	<b>CEILING TYPE</b>	<b>DOOR</b>	<b>SHIELDING</b>	<b>VOLTAGE</b>		
<b>M46</b> Specification Grade Circular Regressed Static Troffer	<b>2</b> Two <b>4</b> Four <b>6</b> Six <b>8</b> Eight  See Product Availability table below.	<b>F</b> Overlap Flange	<b>FS</b> White Flush Steel (Std.)	<b>OP</b> Translucent White Lens	<b>U</b> 120V-277V <b>347</b> 347V		
<b>SIZE</b>	<b>LAMP TYPE</b>	<b>BALLAST</b>	<b>OPTIONS</b>				
<b>2</b> 2' Diameter <b>3</b> 3' Diameter <b>4</b> 4' Diameter	<b>14</b> 2', T5: 14 Watt <b>17</b> 2', T8: 17 Watt <b>21</b> 3', T5: 21 Watt <b>24</b> 2', T5HO: 24 Watt <b>25</b> 3', T8: 25 Watt <b>28</b> 4', T5: 28 Watt <b>31U1</b> U-Bent, 1½" Leg Spacing T8: 31 Watt <b>32</b> 4', T8: 32, 30, 28 or 25 Watt <b>32U6</b> U-Bent, 6" Leg Spacing T8: 32 Watt <b>39</b> 3', T5HO: 38 Watt <b>40TT</b> Twin Tube Compact, 2G11 Base: 40 Watt <b>54</b> 4', T5HO: 54 or 51 Watt	<b>NOTE:</b> See Technical Section for other ballast options. <b>E</b> Electronic T8, Instant Start <b>3E</b> 3-Lamp Electronic T8, Instant Start <b>4E</b> 4-Lamp Electronic T8, Instant Start <b>24E</b> (1) 2-Lamp and (1) 4-Lamp Electronic T8, Instant Start <b>EP</b> Electronic T5 or T8, Programmed Start <b>3EP</b> 3-Lamp Electronic T5HO or T8, Programmed Start <b>4EP</b> 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start	<b>EL</b> Emergency Battery Pack <b>GLR</b> Fast Blow Fuse <b>NYC</b> NYC Compliant <b>NYCU</b> NYC Compliant, Union Label				

### PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	HEIGHT
2' Diameter	2	31U1, 32U6, 40TT	9"
	4	14, 17, 24	9"
	6	14, 17, 24	9"
3' Diameter	4	21, 25, 39	9"
	6	21, 25, 39	9"
4' Diameter	4	28, 32, 54	9"
	6	28, 32, 54	9"
	8	28, 32, 54	9"
	8	28, 32, 54	9"

Note: M46 must be installed prior to ceiling.

