

P2

High Efficiency Static Parabolic

PARABOLICS






FEATURES

- 3" deep cell louver combined with maximum luminous opening, ideal for retail environments
- Meets IES standard RP-1 glare control recommendations on various models
- Ideal for today's computer intensive office
- Wide light distribution provides uniform illumination
- Utilizes the entire opening of the module to maximize light output
- Anodized low iridescent aluminum louver
- Surface and pendant mount available
- UL listed 1598, cUL or CSA. Damp Location standard

ORDERING INFORMATION

P2							
MODEL	NO. OF LAMPS	CEILING TYPE	CELLS WIDE BY CELLS LONG	AIR FUNCTIONS	AIR CONTROL	VOLTAGE	
P2 High Efficiency Static Parabolic	1 One 2 Two 3 Three 4 Four <small>See Product Availability table below.</small>	G Grid F Overlap Flange M Modular Fit-in Trim SM Surface Mount (Static only)	See Product Availability table below.	S Static H Heat Extract	Blank None D Extract Dampers	U 120V-277V 347 347V	
SIZE	LAMP TYPE	LOUVER FINISH	BALLAST	OPTIONS			
94 9" x 4'	17 2', T8: 17 Watt	LD Low Iridescent Semi-Specular (Std.)	NOTE: See Technical Section for other ballast options. E Electronic T8, Instant Start	F0735 35K 75CRI T8 Lamps Installed			
14 1' x 4'	28 4', T5: 28 Watt	LS Low Iridescent Specular	3E 3-Lamp Electronic T8, Instant Start	F0835 35K 82CRI T8 Lamps Installed			
22 2' x 2'	31U1 U-Bent, 1 5/8" Leg Spacing T8: 31 Watt	MA Matte Anodized Low Iridescent Semi-Specular Aluminum	4E 4-Lamp Electronic T8, Instant Start	F5835 35K 85CRI T5 Lamps Installed			
24 2' x 4'	32 4', T8: 32, 30, 28 or 25 Watt		24E (1) 2-Lamp and (1) 4-Lamp Electronic T8, Instant Start	2BC Two Ballast Covers			
	32U6 U-Bent, 6" Leg Spacing T8: 32 Watt		EP Electronic T5 or T8, Programmed Start	C388 3-Wire Flex			
	40TT Twin Tube Compact, 2G11 Base: 40 Watt		3EP 3-Lamp Electronic T5HO or T8, Programmed Start	C488 4-Wire Flex			
	54 4', T5HO: 54 or 51 Watt		4EP 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start	EL Emergency Battery Pack			
			ETT Electronic Twin Tube, Instant Start (Specify voltage)	GLR Fast Blow Fuse			
				GMF Slow Blow Fuse			
				MS9 Master/Satellite w/9' Harness			
				PAF Paint After Fabrication			

For other options see pages 96-112.



PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	LOUVER CONFIGURATIONS
9" x 4'	1	28, 32, 54	1 x 10 (10)
	2	28, 32, 54	1 x 10 (10)
1' x 4'	1	28, 32, 54	1 x 8 (8)
	2	28, 32, 54	1 x 8 (8)
2' x 2'	2	17, 31U1, 32U6, 40TT	3 x 3 (9) , 4 x 4 (16)
	3	17, 31U1, 40TT	3 x 3 (9) , 4 x 4 (16)
2' x 4'	2	28, 32, 54	2 x 6 (12) , 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)
	3	28, 32, 54	3 x 6 (18) , 3 x 8 (24), 4 x 6 (24)
	4	28, 32, 54	2 x 6 (12) , 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)

Standard louver configurations shown in bold. For other lamp or louver configurations, contact your local Columbia Lighting representative. Various options may increase fixture height on 2' x 2' units. Contact your Columbia Lighting representative if plenum depth is a concern.