

## High Efficiency Static Parabolic

### FEATURES

- 3" deep cell louver combined with maximum luminous opening, ideal for retail environments
- Meets IES standard RP-1 glare control recommendations on various models
- Ideal for today's computer intensive office
- Wide light distribution provides uniform illumination
- Utilizes the entire opening of the module to maximize light output
- Anodized low iridescent aluminum louver
- White powder coat finish painted after fabrication
- Surface and pendant mount available
- UL listed 1598, cUL or CSA. Damp Location standard



### ORDERING INFORMATION

<b>P2</b>											
MODEL	NO. OF LAMPS	CEILING TYPE	CELLS WIDE BY CELLS LONG	AIR FUNCTIONS	AIR CONTROL	VOLTAGE	SIZE	LAMP TYPE	LOUVER FINISH	BALLAST	OPTIONS
<b>P2</b> High Efficiency Static Parabolic	<b>1</b> One <b>2</b> Two <b>3</b> Three <b>4</b> Four <small>See Product Availability table below.</small>	<b>G</b> Grid <b>F</b> Overlap Flange <b>M</b> Modular Fit-in Trim <b>SM</b> Surface Mount (Static only)	<small>See Product Availability table below.</small>	<b>S</b> Static <b>H</b> Heat Extract	<b>Blank</b> None <b>D</b> Extract Dampers	<b>U</b> 120V-277V <b>347</b> 347V	<b>94</b> 9" x 4' <b>14</b> 1' x 4' <b>22</b> 2' x 2' <b>24</b> 2' x 4'	<b>17</b> 2', T8: 17 Watt <b>28</b> 4', T5: 28 Watt <b>31U1</b> U-Bent, 1 5/8" Leg Spacing T8: 31 Watt <b>32</b> 4', T8: 32, 30, 28 or 25 Watt <b>32U6</b> U-Bent, 6" Leg Spacing T8: 32 Watt <b>40TT</b> Twin Tube Compact, 2G11 Base: 40 Watt <b>54</b> 4', T5HO: 54 or 51 Watt	<b>LD</b> Low Iridescent Semi-Specular (Std.) <b>LS</b> Low Iridescent Specular <b>MA</b> Matte Anodized Low Iridescent Semi-Specular Aluminum	<b>NOTE:</b> See Technical Section for other ballast options. <b>E</b> Electronic T8, Instant Start <b>3E</b> 3-Lamp Electronic T8, Instant Start <b>4E</b> 4-Lamp Electronic T8, Instant Start <b>24E</b> (1) 2-Lamp and (1) 4-Lamp Electronic T8, Instant Start <b>EP</b> Electronic T5 or T8, Programmed Start <b>3EP</b> 3-Lamp Electronic T5HO or T8, Programmed Start <b>4EP</b> 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start <b>ETT</b> Electronic Twin Tube, Instant Start (Specify voltage)	<b>F0735</b> 35K 75CRI T8 Lamps Installed <b>F0835</b> 35K 82CRI T8 Lamps Installed <b>F5835</b> 35K 85CRI T5 Lamps Installed <b>2BC</b> Two Ballast Covers <b>C388</b> 3-Wire Flex <b>C488</b> 4-Wire Flex <b>EL</b> Emergency Battery Pack <b>GLR</b> Fast Blow Fuse <b>GMF</b> Slow Blow Fuse <b>MS9</b> Master/Satellite w/9' Harness <b>PAF</b> Paint After Fabrication

For other options see pages 99-114.

### PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	LOUVER CONFIGURATIONS
9" x 4'	1	28, 32, 54	<b>1 x 10 (10)</b>
	2	28, 32, 54	<b>1 x 10 (10)</b>
1' x 4'	1	28, 32, 54	<b>1 x 8 (8)</b>
	2	28, 32, 54	<b>1 x 8 (8)</b>
2' x 2'	2	17, 31U1, 32U6, 40TT	<b>3 x 3 (9), 4 x 4 (16)</b>
	3	17, 31U1, 40TT	<b>3 x 3 (9), 4 x 4 (16)</b>
2' x 4'	2	28, 32, 54	<b>2 x 6 (12), 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)</b>
	3	28, 32, 54	<b>3 x 6 (18), 3 x 8 (24), 4 x 6 (24)</b>
	4	28, 32, 54	<b>2 x 6 (12), 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)</b>

Standard louver configurations shown in bold. For other lamp or louver configurations, contact your local Columbia Lighting representative. Various options may increase fixture height on 2' x 2' units. Contact your Columbia Lighting representative if plenum depth is a concern.

