

## Recessed Air Handling Parabolic

### FEATURES

- 3" deep cell parabolic louver for optimum control
- IES standard RP-1 glare control models available
- Wide light distribution provides uniform illumination
- Black reveal with full air handling capabilities
- Anodized low iridescent aluminum louver
- Treated with a five stage phosphate bonding process and finished with a baked white enamel
- Mechanical light trap prevents light leaks
- Surface mount available
- UL listed 1598, cUL or CSA. Damp Location standard



### ORDERING INFORMATION

| <b>P4</b>   | -  |   | -  |   | -   |   | - |  | - |  |
|---|--|---|--|---|---|---|---|--|---|--|
| MODEL   | NO. OF LAMPS   | CEILING TYPE  | CELLS WIDE BY CELLS LONG   | AIR CONTROL   | VOLTAGE   | OPTIONS   |   |  |   |  |
| <b>P4</b> Recessed Air Handling Parabolic                   | <b>1</b> One<br><b>2</b> Two<br><b>3</b> Three<br><b>4</b> Four<br>See Product Availability table below.   | <b>G</b> Grid<br><b>F</b> Overlap Flange<br><b>M</b> Modular Fit-in Trim<br><b>SM</b> Surface Mount (Static only)<br><b>SG</b> Slot Grid                                      | See Product Availability table below.  | <b>Blank</b> None<br><b>V</b> Supply Vanes<br><b>D</b> Extract Dampers<br><b>VD</b> Vanes & Dampers<br>For information about air handling and controls see page 103.  | <b>U</b> 120V-277V<br><b>347</b> 347V                         | <b>F0735</b> 35K 75CRI T8 Lamps Installed<br><b>F0741</b> 41K 75CRI T8 Lamps Installed<br><b>F0835</b> 35K 82CRI T8 Lamps Installed<br><b>F5835</b> 35K 85CRI T5 Lamps Installed<br><b>2BC</b> Two Ballast Covers<br><b>C388</b> 3-Wire Flex<br><b>C488</b> 4-Wire Flex<br><b>EL</b> Emergency Battery Pack<br><b>GLR</b> Fast Blow Fuse<br><b>GMF</b> Slow Blow Fuse<br><b>M4R</b> 95% Reflective Specular Aluminum Insert<br><b>MS9</b> Master/Satellite w/9' Harness<br><b>PAF</b> Paint After Fabrication<br><b>SRA</b> Specular Anodized Aluminum Reflector<br><b>NYC</b> NYC Compliant<br><b>NYCU</b> NYC Compliant, Union Label<br>For other options see pages 96-112. |   |  |   |  |
| SIZE  | LAMP TYPE  | LOUVER FINISH   | AIR FUNCTIONS  | BALLAST   | <b>NOTE:</b> See Technical Section for other ballast options. |   |   |  |   |  |
| <b>14</b> 1' x 4'<br><b>22</b> 2' x 2'<br><b>24</b> 2' x 4' | <b>17</b> 2', T8: 17 Watt<br><b>28</b> 4', T5: 28 Watt<br><b>31U1</b> U-Bent, 1½" Leg Spacing T8: 31 Watt<br><b>32</b> 4', T8: 32, 30, 28 or 25 Watt<br><b>32U6</b> U-Bent, 6" Leg Spacing T8: 32 Watt<br><b>40TT</b> Twin Tube Compact, 2G11 Base: 40 Watt<br><b>54</b> 4', T5HO: 54 or 51 Watt | <b>GW</b> Gloss White Enamel<br><b>LD</b> Low Iridescent Semi-Specular<br><b>LS</b> Low Iridescent Specular<br><b>MA</b> Matte Anodized Low Iridescent Semi-Specular Aluminum | <b>S</b> Static<br><b>A</b> Air Handling<br><b>C</b> Combination Supply/Extract<br><b>H</b> Heat Extract | <b>E</b> Electronic T8, Instant Start<br><b>3E</b> 3-Lamp Electronic T8, Instant Start<br><b>4E</b> 4-Lamp Electronic T8, Instant Start<br><b>EP</b> Electronic T5 or T8, Programmed Start<br><b>3EP</b> 3-Lamp Electronic T5HO or T8, Programmed Start<br><b>4EP</b> 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start<br><b>ETT</b> Electronic Twin Tube, Instant Start (Specify voltage)<br><b>ELW</b> Electronic T8, 0.77 Ballast Factor, Low Wattage, Instant Start<br><b>3ELW</b> 3-lamp Electronic T8, 0.77 Ballast Factor, Low Wattage, Instant Start |   |   |   |  |   |  |

### PRODUCT AVAILABILITY

| SIZE    | NO. OF LAMPS | LAMP TYPE            | LOUVER CONFIGURATIONS  |
|---------|--------------|----------------------|--|
| 1' x 4' | 1            | 28, 32, 54           | <b>1 x 6 (6), 1 x 8 (8), 1 x 9 (9), 2 x 6 (12), 2 x 8 (16)</b> |
|         | 2            | 28, 32, 54           | <b>1 x 6 (6), 1 x 8 (8), 1 x 9 (9), 2 x 6 (12), 2 x 8 (16)</b> |
| 2' x 2' | 2            | 17, 31U1, 32U6, 40TT | <b>3 x 3 (9), 4 x 4 (16)</b>                                   |
|         | 3            | 17, 31U1, 40TT       | <b>3 x 3 (9), 4 x 4 (16)</b>                                   |
| 2' x 4' | 2            | 28, 32, 54           | <b>2 x 6 (12), 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)</b>          |
|         | 3            | 28, 32, 54           | <b>3 x 6 (18), 3 x 8 (24)</b>                                  |
|         | 4            | 28, 32, 54           | <b>2 x 6 (12), 2 x 8 (16), 4 x 6 (24), 4 x 8 (32)</b>          |

Standard louver configurations shown in bold. For other lamp or louver configurations, contact your local Columbia Lighting representative. Various options may increase fixture height on 2' x 2' units. Contact your Columbia Lighting representative if plenum depth is a concern.

