

FEATURES

- Completely recessed housing and light basket
- One, two, or three lamp cross sections
- Available for linear or compact fluorescent lamps; T8, T5, T5HO, 40TT or 50TT
- Plastic end caps support the light basket and act as a light seal
- Light basket and reflector are powder coated white and painted after fabrication
- Easy installation and maintenance
- UL listed 1598, cUL or CSA. Damp Location standard



ORDERING INFORMATION

STR					MPO				
MODEL STR Stratus Recessed Indirect	NO. OF LAMPS IN CROSS SECTION 1 Once 2 Two 3 Three See Product Availability table below.	CEILING TYPE G Grid Lay-in SG Slot Grid SM Surface Mount	AIR FUNCTION Blank Static A Air Handling	VOLTAGE U 120V-277V 347 347V	SIZE 14 1' x 4' 22 2' x 2' 24 2' x 4'	LAMP TYPE 14 2', T5: 14 Watt 17 2', T8: 17 Watt 24 2', T5HO: 24 Watt 28 4', T5: 28 Watt 32 4', T8: 32, 30, 28 or 25 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 or 51 Watt	SHIELDING MPO Metal Perf w/Overlay	BALLAST NOTE: See Technical Section for other ballast options. E Electronic T8, Instant Start ED Electronic Dimming T8 and T5 EP Electronic T5, T5HO, or T8, Programmed Start ETT Electronic Twin Tube, Instant Start	OPTIONS EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse NYC NYC Compliant NYCU NYC Compliant, Union Label
ACCESSORIES (ORDER SEPARATELY) FK14 1' x 4' Flange Kit FK22 2' x 2' Flange Kit FK24 2' x 4' Flange Kit									

PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS IN CROSS SECTION	NO. OF LAMPS IN FIXTURE	LAMP TYPE	HEIGHT
1' x 4'	1	1	28, 32, 54	5 3/4"
	1	1	40TT	5 3/4"
	2	2	28, 32, 54	5 3/4"
	3	3	28, 32, 54	5 3/4"
2' x 2'	2	2	14, 17, 24, 40TT	5 3/4"
	3	3	14, 17, 24, 40TT	5 3/4"
2' x 4'	2	2	28, 32, 54	5 3/4"
	2	4	40TT	5 3/4"
	3	3	28, 32, 54	5 3/4"
	3	6	40TT	5 3/4"

