

## Stratus® Side Basket with Louver

### FEATURES

- High performance louver, accentuated by softly glowing perforated side baskets
- True parabolic louver directs light with pinpoint precision and reduces glare
- Direct component dramatically increases efficiency when compared to other side basket recessed indirects
- Contractor friendly; easy to install and maintain
- Light reflector and baskets are powder coated after fabrication
- UL listed 1598, cUL or CSA. Damp Location standard



### ORDERING INFORMATION

<b>STSL</b>	-		-		-	<b>MPO</b>	-		-		-	
<b>MODEL</b> STSL Stratus® Side Basket with Louver	<b>NO. OF LAMPS IN CROSS SECTION</b> 1 One 2 Two 4 Four See Product Availability table below.		<b>CEILING TYPE</b> G Grid Lay-in SG Slot Grid SM Surface Mount	<b>SHIELDING</b> MPO Metal Perf w/Overlay	<b>AIR FUNCTION</b> Blank Static A Air Handling	<b>VOLTAGE</b> U 120V-277V 347 347V						
<b>SIZE</b> 14 1' x 4' 22 2' x 2' 24 2' x 4'	<b>LAMP TYPE</b> 14 2', T5: 14 Watt 17 2', T8: 17 Watt 24 2', T5H0: 24 Watt 28 4', T5: 28 Watt 32 4', T8: 32, 30, 28 or 25 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5H0: 54 or 51 Watt	<b>LOUVER FINISH</b> GW Gloss White Enamel LS Low Iridescent Specular Parabolic Louver MA Matte Anodized Low Iridescent Semi-Specular Aluminum M4R 95% Reflective Specular Aluminum	<b>BALLAST</b> <b>NOTE:</b> See Technical Section for other ballast options. E Electronic T8, Instant Start ED Electronic Dimming T8 and T5 EP Electronic T5, T5H0, or T8, Programmed Start ETT Electronic Twin Tube, Instant Start	<b>OPTIONS</b> EL Emergency Battery Pack GLR Fast Blow Fuse GMF Slow Blow Fuse NYC NYC Compliant NYCU NYC Compliant, Union Label								
<b>ACCESSORIES (ORDER SEPARATELY)</b> FK14 1' x 4' Flange Kit FK22 2' x 2' Flange Kit FK24 2' x 4' Flange Kit												

### PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS IN CROSS SECTION	NO. OF LAMPS IN FIXTURE	LAMP TYPE	HEIGHT
1' x 4'	1	1	28, 32, 54	5 3/4"
	1	2	40TT	5 3/4"
	2	2	28, 32, 54	5 3/4"
2' x 2'	2	2	14, 17, 24	5 3/4"
	2	2	40TT	5 3/4"
	4	4	14, 17, 24	5 3/4"
2' x 4'	2	2	28, 32, 54	5 3/4"
	2	4	40TT	5 3/4"
	4	4	28, 32, 54	5 3/4"

