

Wet Location Lensed Troffer

FEATURES

- Wet label shallow housing troffer
- Gasketed to provide additional seal between door, lens, and housing
- Mitered corners standard on door frame
- Rolled or hemmed housing edges
- Mechanical light trap
- Metal parts are white powder coat, painted after fabrication
- UL listed 1598, cUL or CSA. Wet Location standard



ORDERING INFORMATION

WT									
MODEL	NO. OF LAMPS	CEILING TYPE	SHIELDING	VOLTAGE	SIZE	LAMP TYPE	DOOR	BALLAST	OPTIONS
WT Wet Location Lensed Troffer	1 One 2 Two 3 Three 4 Four 6 Six See Product Availability table below.	G Inverted T-Bar F Overlap Flange	A12 Pattern 12 Acrylic Lens A12125 Pattern 12 Acrylic Lens, 0.125" Nominal A19 Pattern 19 Acrylic Lens, 0.156" Nominal DR12 Pattern 12 Acrylic Lens, Impact Resistant, 0.140" For more shielding options see page 40.	U 120V-277V 347 347V	14 1' x 4' 22 2' x 2' 24 2' x 4'	14 2', T5: 14 Watt 17 2', T8: 17 Watt 24 2', T5HO: 24 Watt 28 4', T5: 28 Watt 31U1 U-Bent, 1½" Leg Spacing T8: 31 Watt 32 4', T8: 32, 30, 28 or 25 Watt 32U6 U-Bent, 6" Leg Spacing T8: 32 Watt 40TT Twin Tube Compact, 2G11 Base: 40 Watt 54 4', T5HO: 54 or 51 Watt	FA White Flush Aluminum RA White Regressed Aluminum	NOTE: See Technical Section for other ballast options. E Electronic T8, Instant Start 3E 3-lamp Electronic T8, Instant Start 4E 4-Lamp Electronic T8, Instant Start 24E (1) 2-Lamp and (1) 4-Lamp Electronic T8, Instant Start EP Electronic T5 or T8, Programmed Start 3EP 3-lamp Electronic Programmed Start (T8, T5HO) Others available. 4EP 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start EPTT Electronic Twin Tube, Programmed Start	F0735 35K 75CRI T8 Lamps Installed F0835 35K 82CRI T8 Lamps Installed F5835 35K 85CRI T5 Lamps Installed GLR Fast Blow Fuse NYC NYC Compliant NYCU NYC Compliant, Union Label

PRODUCT AVAILABILITY

SIZE	NO. OF LAMPS	LAMP TYPE	GRID TRIM HEIGHT
1' x 4'	1	32	4 ⁷ / ₈ "
	2	28, 32, 54	4 ¹ / ₄ "
	3	32	4 ⁷ / ₈ "
2' x 2'	2	14, 17, 24, 31U1, 32U6, 40TT	4 ¹ / ₄ "
	3	14, 17, 24, 31U1, 40TT	4 ¹ / ₄ "
	4	14, 17, 24	4 ¹ / ₄ "
2' x 4'	2	28, 32, 54	3 ³ / ₄ "
	3	28, 32, 54	3 ³ / ₄ "
	4	28, 32, 54	3 ³ / ₄ "
	6	28, 32, 54	3 ³ / ₄ "

