

Enclosed and Gasketed Acrylic Tube, Severe Environment

EXTREME ENVIRONMENT

FEATURES

- Suitable for wet locations
- NSF Certified, Splash Zone Food Processing
- NEMA 4X hose down
- 0.125" thick extruded clear acrylic enclosure
- Endcaps – 18 GA., spun 304 stainless steel with silicone gasket
- 95% reflective specular aluminum or painted gloss white reflector (minimum reflectance 88%)
- 72" of 16/3 SJ30 cord installed with straight male cord connector (rated IP67) in End Cap; other end of cord less plug, is supplied as standard
- Two stainless steel straps (allows suspension anywhere along enclosure) supplied standard
- Optional wall mounting bracket kit available



ORDERING INFORMATION

| XTS | 2 | | U | | |
|---|---|--|--------------------|--|--|
| MODEL | NO. OF LAMPS IN CROSS SECTION | REFLECTOR | VOLTAGE | LAMPS INSTALLED | OPTIONS |
| XTS Enclosed and Gasketed Acrylic Tube, Severe Environment | 2 Two See Product Availability table below. | M4R 95% Reflective Specular Aluminum (Narrow Beam) GW Gloss White (Wide Beam) | U 120V-277V | F0841 41K 82CRI 32W T8 Lamps Installed F5841 41K 85CRI 54W T5HO Lamps Installed | F3C6WT 6' Mini-Quick disconnect cord set. Threaded male receptacle, strain relief installed in end cap. Straight threaded female plug one end of cord, other end has stripped leads ready for feed installation F3C12WT 12' Mini-Quick disconnect cord set. Threaded male receptacle, strain relief installed in end cap. Straight threaded female plug one end of cord, other end has stripped leads ready for feed installation GLR Fast Blow Fuse GMF Slow Blow Fuse |
| SIZE | LAMP TYPE | BALLAST* | | | |
| 4 4' | 32 4', T8: 32, 30, 28, or 25 Watt | NOTE: See Technical Section for other ballast options. | | | |
| 8 8' | 54 4', T5HO: 54 or 51 Watt | E (1) 2-Lamp Electronic T8, Instant Start 4E (1) 4-Lamp Electronic T8, Instant Start EHL (1) 2-Lamp Electronic T8, High Light Output, Instant Start 4EHL (1) 4-Lamp Electronic T8, High Light Output, Instant Start EP (1) 2-Lamp Electronic T5, Programmed Start 4EP (1) 4-Lamp Electronic T5HO, Programmed Start EPHL (1) 2-Lamp Electronic T8, High Light Output, Programmed Start 4EPHL (1) 4-Lamp Electronic T8, High Light Output, Programmed Start | | | |

*For NEMA premium ballast, add prefix N. e.g., **NEPHL**.

PRODUCT AVAILABILITY

| SIZE | NO. OF LAMPS IN CROSS SECTION | NO. OF LAMPS | LAMP TYPE | DIAMETER | LENGTH |
|------|-------------------------------|--------------|-----------|----------|--------|
| 4' | 2 | 2 | 32, 54 | 6 1/4" | 50" |
| 8' | 2 | 4 | 32, 54 | 6 1/4" | 97" |

