



**FEATURES**

- Reflectors have 15% uplight
- Spring loaded turret lampholders
- 6" lamp spacing
- For individual or continuous row mounting
- Channel ends double as joiners
- Full depth end closures available

**PROJECT INFORMATION**

Project Name \_\_\_\_\_

Type \_\_\_\_\_

Catalog No. \_\_\_\_\_

Date \_\_\_\_\_

**CONSTRUCTION**

Heavy steel housing with longitudinal reinforcing ribs for extra strength.

**FINISH**

White painted parts are treated with a five stage phosphate bonding process and finished with a high reflectance baked enamel.

**ELECTRICAL**

Standard class "P", thermally protected, auto-resetting HPF ballast, sound rated A. All ballast leads extend a minimum of 6" through access location. NEC/CEC-compliant ballast disconnect is standard.

**CERTIFICATION**

All luminaires are built to UL 1598 standards and bear appropriate UL and cUL or CSA labels. Damp location labeling is standard. Emergency-equipped fixtures labeled UL 924.

**ORDERING INFORMATION**

**EXAMPLE KL8-96-U-EU**

KL						E				
MODEL	SIZE	NO. OF LAMPS IN CROSS SECTION	LAMP TYPE	REFLECTOR TYPE	VOLTAGE	OPTIONS				
KL Premium Industrial	4 4' 8 8'	2 Two 3 Three 4 Four	48 4', T12: 40 Watt 59 8', T8 Slimline: 59 Watt 96 8', T12: 75 or 60 Watt	U Apertured Reflector for Uplight (Standard) ST Solid Top (No Uplight) SLR Specular Reflector with Uplight SLRST Specular Reflector Solid Top	U 120V-277V 347 347V	GLR Fast Blow Fuse GMF Slow Blow Fuse EL Emergency Battery Pack BC Branch Circuit Plug-on Wiring System (See options section for details.) PAF Paint After Fabrication NYC NYC Compliant NYCU NYC Compliant, Union Label	<b>ACCESSORIES (ORDER SEPARATELY)</b>			
					<b>BALLAST</b>					
					E Electronic T8, Instant Start For others available, see Ballast Options.	<b>KZT</b> Zip Tee Hanger - 1½" spacer on T-bar ceiling <b>KTH</b> Slide Clamp Tong Hanger <b>S18</b> 18" Stem, canopy and 8° aligner <b>SS18</b> 18", 45° Swivel Stem & Canopy <b>KHC</b> 24" Chain Hanging Assembly <b>KLEC</b> Full Depth End Closure <b>KLWG4</b> Wire Guard 4' lg. - 2 required per 8' fixture <b>KLEGG</b> White Straight Blade Egg Crate Louver 4' - 2 required per 8' fixture				

